

INDUSTRIAL FILTER ULTRASONIC CLEANER

Features:

- * With BLT type industrial ultrasonic transducers
- * Tank material:SUS304, T=2.0mm. Human hand argon welded, Sturdy and durable resistance to high temperature
- * Inset generator / External generator
- * Ultrasonic power adjust, suit for different object clean
- * Actual temperature with constant temp control system
- * Count-down time with LCD display: 1~99mins/24H keep working
- * With power off memory function for time & temperature
- * With FILTRATION system for recycle use liquid & avoid secondary pollution
- * Accessories: Machine with stainless steel basket, drainage, lid, movable castors.



Technical parameters:

Model	LS-1201F	LS-1801F	LS-2401F	LS-3001F	LS-3601F	LS-4801F	LS-6001F	LS-7201F
Tank Dimension (mm)	500x300x250	500x350x350	550x400x400	600x450x400	600x500x450	700x500x500	800x600x550	1000x600x600
Max. Capacity	37L	61L	88L	108L	135L	175L	264L	360L
Material	SUS304 (Mirror shining image available)							
Transducer No.	12pcs	18pcs	24pcs	30pcs	36pcs	48pcs	60pcs	72pcs
Ultrasonic power (Max.)	600W	900W	1200W	1500W	1800W	2400W	3000W	3600W
Ultrasonic frequency	28/40kHz	28/40kHz	28/40kHz	28/40kHz	28/40kHz	28/40kHz	28/40kHz	28/40kHz
Temperature	normal~95°C adjustable							
Heating power	1.5KW	1.5KW	3KW	4.5KW	4.5KW	6KW	6KW	9KW
Timer	0~999min	0~999min	0~999min	0~999min	0~999min	0~999min	0~999min	0~999min
Machine voltage	AC110V/AC220V, 1phase				AC220V/AC380V, 3phase			
Generator Voltage	AC110V / 220V 1phase							
Features	With filtration system (oil catch can, filter bag); with basket & lid							

Remark: customized tank dimension and power are available.